



TITEBOND III ULTIMATE WOOD GLUE

Titebond III Ultimate is a single component, water resistant glue. Titebond III is non-toxic, solvent-free and cleans up with water - safer to use than traditional waterproof wood glues. Provides strong initial adhesion and sands easily. The ultimate in wood glues - ideal for both indoor and outdoor applications.

Key Features

- Glue both internal and external applications
- Water resistant
- Great adhesive power
- Offers excellent sanding
- Non-toxic and easy to clean with water

Technical specifications

- Application temperature: above 8 ° C
- Setting time: about 10 minutes at 20 ° C
- Final fixing time: 20-25 minutes at 20 ° C
- Coverage: approx. 6 m² x liter
- Method of application: directly from the bottle or by brush / roller
- Cleaning: with a damp cloth when the glue is still wet. With a scraper or sandpaper when dry
- Limitations: Titebond III glue is not to be used for applications that require constant immersion in water. Do not use for structural applications. Do not use at temperatures below 10 ° C. Store the product at temperatures below 25 ° C. Shake before using. Due to the low pH level, this product can cause corrosion of metal surfaces: test the product before use.

SPECIFICHE

SKU	Packaging
53051	118 ML
53052	237 ML
53053	473 ML
53054	946 ML
53055	3800 ML