



NABERTHERM KILN N 1000/H

The Nabertherm N 1000/H chamber kiln offers 1000 L capacity and fires to 1340 °C; five-sided support-tube heating ensures excellent uniformity, while a SiC hearth, CLP-free double insulation and optimized airflow deliver energy-efficient reliability for studios, schools and labs, with MyNabertherm monitoring and Solar Mode. **Key features**

- Even five-sided heating
- Service-friendly support-tube elements
- Protective silicon-carbide floor
- Double insulation, non-carcinogenic materials
- Optimized ventilation for rapid cooling
- MyNabertherm app & Solar Mode

Technical specifications

- Chamber volume: 1000 L
- Maximum temperature: 1340 °C (continuous ≤ 1230 °C)
- Power supply: 400 V, 3-phase, ~10 kW
- Controller: AC590, 6.8" touch, 50 programs, Wi-Fi/USB
- SiC hearth + double-layer insulation

SPECIFICHE

SKU	Computer type	Capacity	Max. Temp	Power	Voltage
58239	B500	1000	1340°C	75 Kw	380 ~ 400 V - 50 HZ

DIMENSIONS

SKU	Internal Width	Internal Depth	Internal Height	Length	Height	Depth	Weight in kg
58239	800	1000	1250	1390	2140	1850	2320