



NABERTHERM KILNE NE 70/L

Perfect for ceramics, glass decoration and small fusing jobs, the Nabertherm NE 70/L 70 L electric chamber kiln delivers outstanding temperature uniformity, quick firing cycles and low operating costs thanks to protected elements, optimised insulation and smart digital control, while remote monitoring via the MyNabertherm app makes it the professional, energy-efficient choice. **Key features**

- Protected groove-mounted heating elements
- Bilateral heating for even temperature
- Continuously adjustable air inlet and Ø80 mm exhaust
- Solar Mode ready for photovoltaic power
- Online monitoring via MyNabertherm app
- Bench-top design with optional stand

Technical specifications

- Power supply: 400 V 3-phase; installed load 7.0 kW
- Chamber volume: 70 L; max temperature 1320 °C
- Exhaust connection: Ø80 mm fitting included
- Eco insulation free of carcinogenic fibres (CE 1272/2008)
- AC590 controller: 6.8" touch, 50 programs, 40 ramps, Wi-Fi/USB
- Furniture set (shelves and posts) sold separately

SPECIFICHE

SKU	Computer type	Capacity	Max. Temp	Power	Voltage
24416	AC590	70	1200°C	2,9 Kw	220 ~ 230 V - 50 HZ

DIMENSIONS

SKU	Internal Width	Internal Depth	Internal Height	Length	Height	Depth	Weight in kg
24416	400	380	450	690	700	850	120