



## NABERTHERM KILNE NE 70/R

Ideal for ceramics, glass or porcelain decoration and small fusing projects, the Nabertherm NE 70/R 70 L electric chamber kiln delivers fast cycles, low energy use and even heat distribution thanks to protected elements, optimised insulation and the AC590 digital controller with remote monitoring via the MyNabertherm app. **Key features**

- Protected groove-mounted heating elements
- Bilateral heating for uniform temperature
- Adjustable air inlet and Ø80 mm exhaust
- Solar Mode ready for photovoltaic power
- Online monitoring via MyNabertherm app
- Bench-top design with optional stand

### Technical specifications

- Power supply: 400 V 3-phase; installed load 7 kW
- Chamber volume: 70 L; max temperature 1320 °C
- Exhaust connection: Ø80 mm fitting included
- Eco insulation free of carcinogenic fibres (CE 1272/2008)
- AC590 controller: 6.8" touch, 50 programs, 40 ramps, Wi-Fi/USB
- Furniture set (shelves and posts) sold separately

### SPECIFICHE

SKU	Computer type	Capacity	Max. Temp	Power	Voltage
24422	AC590	70	1300°C	5,5 Kw	380 ~ 400 V - 50 HZ

### DIMENSIONS

SKU	Internal Width	Internal Depth	Internal Height	Length	Height	Depth	Weight in kg
24422	400	380	450	690	700	850	120