



NABERTHERM KILNE NE 100

Designed for ceramics, glass or porcelain decoration and light fusing tasks, the Nabertherm NE 100 100 L electric chamber kiln delivers exceptional temperature uniformity, fast firing cycles and low running costs thanks to groove-protected elements, optimised insulation and the AC590 digital controller, while remote monitoring via the MyNabertherm app ensures professional, energy-efficient results. **Key features**

- Protected groove-mounted heating elements
- Bilateral heating for uniform temperature
- Continuously adjustable air inlet and Ø80 mm exhaust
- Solar Mode ready for photovoltaic power
- Online monitoring via MyNabertherm app
- Bench-top design with optional stand

Technical specifications

- Power supply: 400 V 3-phase; installed load 9.0 kW
- Chamber volume: 100 L; max temperature 1320 °C
- Exhaust connection: Ø80 mm fitting included
- Eco insulation free of carcinogenic fibres (CE 1272/2008)
- AC590 controller: 6.8" touch, 50 programs, 40 ramps, Wi-Fi/USB
- Furniture set (shelves and posts) sold separately

SPECIFICHE

SKU	Computer type	Capacity	Max. Temp	Power	Voltage
24425	AC590	100	1300°C	7,0 Kw	380 ~ 400 V - 50 HZ

DIMENSIONS

SKU	Internal Width	Internal Depth	Internal Height	Length	Height	Depth	Weight in kg
24425	460	440	500	750	750	910	150