



NABERTHERM KILNE NE 280

Designed for schools, institutes and ceramic workshops, the Nabertherm NE 280 280 L electric chamber kiln combines three-sided heating, high-efficiency insulation and the AC590 digital controller to deliver professional temperature uniformity, fast cycles and low energy consumption, with remote monitoring via the MyNabertherm app and Solar Mode compatibility. **Key features**

- Three-sided heating for even temperature
- Groove-protected heating elements
- Stand included as standard
- Adjustable air valve and Ø80 mm exhaust
- Online monitoring & Solar Mode
- Eco insulation free of carcinogenic fibres

Technical specifications

- Power supply: 400 V 3-phase; installed load 15.0 kW
- Chamber volume: 280 L; max temperature 1320 °C
- Exhaust connection: Ø80 mm fitting included
- Optimised insulation for reduced consumption
- AC590 controller: 6.8" touch, 50 programs, 40 ramps, Wi-Fi/USB
- Furniture set (shelves & posts) sold separately

SPECIFICHE

| SKU | Computer type | Capacity | Max. Temp | Power | Voltage |
|-------|---------------|----------|-----------|-------|---------------------|
| 24434 | AC590 | 280 | 1300°C | 15 Kw | 380 ~ 400 V - 50 HZ |

DIMENSIONS

| SKU | Internal Width | Internal Depth | Internal Height | Length | Height | Depth | Weight in kg |
|-------|----------------|----------------|-----------------|--------|--------|-------|--------------|
| 24434 | 550 | 580 | 830 | 760 | 1690 | 1050 | 300 |